Dakota

TEXSTYLE

Technical Data

ROLLER PANEL ROMAN

Composition	30% polyester / 70% PVC
Width	3,000mm
Weight	413gsm +/-10%
Thickness	0.72mm +/-5%
Opacity/Openness	Approx. 6%
Light Fastness	≥ 5 (Blue wool scale)
Coating	Polyester yarns with PVC coating
Flame Retardant	Product is designed and manufactured to comply with Building Code of Australia requirements for class 2 to 9 buildings
Cleaning	Wipe clean with warm soapy water and damp cloth

5 YEAR WARRANTY · SCREEN · ECO FRIENDLY · FLAME RETARDANT

FR · OEKO TEX® STANDARD 100 · GREENGUARD GOLD

Solar Properties

USA Standard Tested To Ashrae 74-73

						Shading Coefficients (Sc)		
	Ts	**Rs**	**As**	**Tv/Vlt**	**O-F**	**3mm CL.**	**6mm CL.**	**9mm CL.**
Quartz	26	63	11	8	6	0.38	0.38	0.34
Marble	25	50	25	5	6	0.37	0.36	0.34
Ore	23	47	30	6	6	0.38	0.37	0.40
Granite	7	4	89	7	6	0.74	0.70	0.51
Flint	10	11	79	8	6	0.70	0.67	0.49
Coal	8	4	88	8	6	0.74	0.70	0.51

Ts Solar Transmittance
Rs Solar Reflection
As Solar Absorbance
Tuv Ultraviolet Transmittance
Tv Visual Light Transmission
O-F Openness Factor
G-Value % Solar Radiation through Fabric
G-Total % Solar Radiation through Blind and Window

Melbourne Head Office
Building 1, Level 2, 630 Mitcham Road
Mitcham VIC 3132 Australia

P +61 3 9729 9970
E **sales@texstyle.com.au**

Learn more at
texstyle.com.au