# Solar View

TEXSTYLE

## Technical Data

ROLLER PANEL ROMAN

| | |
|---|---|
| **Composition** | 30% polyester / 70% PVC |
| **Width** | 3,000mm & 2,500mm |
| **Weight** | 530gsm +/-5% |
| **Thickness** | 0.75mm +/-5% |
| **Opacity/Openness** | ≥ 6 |
| **Light Fastness** | ≥ 5 (Blue wool scale) |
| **Coating** | Polyester yarns with PVC coating |
| **Flame Retardant** | Product is designed and manufactured to comply with Building Code of Australia requirements for class 2 to 9 buildings |
| **Cleaning** | Wipe clean with warm soapy water and damp cloth |

5 YEAR WARRANTY · SCREEN · ECO FRIENDLY · FLAME RETARDANT

FR · OEKO TEX® STANDARD 100 · GREENGUARD GOLD

## Solar Properties

**USA Standard Tested To Ashrae 74-73**

| | Ts | Rs | As | Tv/Vlt | O-F | Shading Coefficients (Sc) 3mm CL. | 6mm CL. | 9mm CL. |
|---|---|---|---|---|---|---|---|---|
| White | 22 | 64 | 14 | 7 | 7 | 0.36 | 0.36 | 0.33 |
| Alabaster | 20 | 61 | 19 | 6 | 6 | 0.38 | 0.38 | 0.34 |
| Off White | 21 | 63 | 16 | 6 | 7 | 0.37 | 0.37 | 0.34 |
| Cotton | 18 | 61 | 21 | 6 | 6 | 0.37 | 0.37 | 0.34 |
| Bone / Off White | 17 | 57 | 26 | 6 | 6 | 0.40 | 0.40 | 0.35 |
| Taupe | 12 | 41 | 47 | 7 | 7 | 0.50 | 0.50 | 0.40 |
| Grey | 12 | 30 | 58 | 7 | 7 | 0.58 | 0.58 | 0.43 |
| Charcoal | 6 | 5 | 89 | 6 | 6 | 0.73 | 0.73 | 0.51 |
| Bronze / Charcoal | 6 | 7 | 87 | 6 | 6 | 0.72 | 0.72 | 0.50 |
| Black / Copper | 7 | 8 | 85 | 7 | 7 | 0.71 | 0.71 | 0.50 |
| Black | 7 | 4 | 89 | 6 | 6 | 0.74 | 0.74 | 0.51 |
| Platinum | 7 | 10 | 83 | 11 | 7 | 0.72 | 0.68 | 0.50 |

**Ts** Solar Transmittance
**Rs** Solar Reflection
**As** Solar Absorbance
**Tuv** Ultraviolet Transmittance
**Tv** Visual Light Transmission
**O-F** Openness Factor
**G-Value** % Solar Radiation through Fabric
**G-Total** % Solar Radiation through Blind and Window

**Melbourne Head Office**
Building 1, Level 2, 630 Mitcham Road
Mitcham VIC 3132 Australia

P +61 3 9729 9970
E **sales@texstyle.com.au**

Learn more at
**texstyle.com.au**