



ROLLER



PANEL



ROMAN

## Technical Data

<b>Composition</b>	100% polyester
<b>Width</b>	3,000mm
<b>Weight</b>	Blockout 430gsm   Light filtering 260gsm
<b>Thickness</b>	Blockout 0.70mm +/-5%   Light filtering 0.60mm +/-5%
<b>Opacity/Openness</b>	Blockout tested to AS-2663-1999
<b>Light Fastness</b>	≥ 7 (Blue wool scale)
<b>Coating</b>	Blockout coated with acrylic foam   Light Filtering stiffened with acrylic
<b>Flame Retardant</b>	Product is designed and manufactured to comply with Building Code of Australia requirements for class 2 to 9 buildings
<b>Cleaning</b>	Surface dust can be removed with vacuum or a soft cloth



MADE IN AUSTRALIA



5 YEAR WARRANTY



BLOCKOUT



LIGHT FILTERING



PVC FREE

## Solar Properties

	European standard tested to DIN EN 410: 2011							Tested to EN 14501	
	Ts	Rs	As	Tv/ Vlt	Tuv	O-F	G-value	Single Glass Reference Glazing A [g window 0.85] [U window 5.7] g-total	High Performance Glass Reference Glazing D [g window 0.32] [U window 1.1] g-total
Owl LF	33	50	17	27	19	0.5	0.37	0.47	0.27
Eland LF	28	47	25	19	10	0.5	0.34	0.48	0.27
Jackal LF	23	41	36	11	7	0.5	0.32	0.50	0.27
Albatross LF	31	52	17	28	15	0.5	0.35	0.45	0.26
Antelope LF	9	24	67	3	2	0.5	0.25	0.58	0.29
Hydrax LF	23	43	34	13	9	0.5	0.31	0.49	0.27
Caribou LF	20	38	42	6	4	0.5	0.31	0.52	0.28
Jackal BO	0	73	27	0	0	0.5	0.06	0.29	0.24

**Ts** Solar Transmittance    **As** Solar Absorbance    **G-Value** % Solar Radiation through Fabric  
**Rs** Solar Reflection    **Tv** Visual Light Transmission    **G-Total** % Solar Radiation through Blind and Window

