

# Vivid Block



## Technical Data

<b>Composition</b>	100% Polyester
<b>Width</b>	2,000mm and 3,000mm
<b>Weight</b>	350gsm +/-5%
<b>Thickness</b>	0.38mm +/-5%
<b>Opacity/Openness</b>	Blockout tested to AS-2663-1999
<b>Light fastness</b>	≥ 5 (Blue wool scale)
<b>Coating</b>	Blockout coated with acrylic foam
<b>Flame Retardant</b>	Tested to AS1530.3
<b>Cleaning</b>	Wipe clean with warm soapy water and damp cloth

## Solar Properties

	European standard tested to DIN EN 410: 2011						Tested to EN 14501	
	Ts	Rs	As	Tv/ Vlt	Tuv	O-F	Single Glass Reference Glazing A [g window 0.85] [U window 5.7] g-total	High Performance Glass Reference Glazing D [g window 0.32] [U window 1.1] g-total
Vividblock	0	6	94	0	0	0	0.68	0.30

**Ts** Solar Transmittance

**As** Solar Absorbance

**Tv** Visual Light Transmission

**G-Value** % Solar Radiation through Fabric

**Rs** Solar Reflection

**Tuv** Ultraviolet Transmittance

**O-F** Openness Factor

**G-Total** % Solar Radiation through Blind and Window

textstyle.com.au

Phone. 03 9729 9970



TEXTSTYLE